

EU Materials Safety Data Sheet to Guideline 91/155/EWG

Date of Issue: 01.04.2004

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

- Product Name: ABS Edgebands
- Manufacturer/Supplier: Döllken-Kunststoffverarbeitung GmbH
Beisenstraße 50
45964 Gladbeck
Tel. +49(0)2043/979-0

2. COMPOSITION / INFORMATION ON INGREDIENTS

Extruded edging from acrylonitrile-butadiene-styrene copolymer (ABS; CAS# 009003-56-9)

3. HAZARDS IDENTIFICATION

This product is not classified as dangerous according to EU criteria

4. FIRST AID MEASURES

No special measures required

5. FIRE-FIGHTING MEASURES

- Extinguishing Media: Water. Synthetic foams. Carbon dioxide. Dry chemical fire extinguishers
- Protection of Fire-fighters: Wear permitted positive pressure self-contained breathing apparatus and protective fire-fighting clothing.
- Particular Hazards from Combustion Products in the Substance: Dense smoke is emitted when burnt without sufficient oxygen. The smoke may contain combustion products of varying composition in addition to carbon dioxide carbon monoxide, and hydrogen, in part of a toxic nature
- Specific Methods of Fire-fighting: Soak thoroughly with water to cool and prevent reignition.

6. ACCIDENTAL RELEASE MEASURES

Not applicable

7. HANDLING AND STORAGE

- Handling:
Note on Safe Handling: Ensure vapour extraction or adequate ventilation during heat processing.
Avoid static electricity
- Storage:
Store in a cool, dry place away from direct sunlight.
Keep away from ignition sources

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Constituent parts with Workplace Exposure Guidelines:
During General Processing : Maximum dust level: Fine dust 3 mg/m³
Total dust 10 mg/m³
Processing at High Temperatures: See Section 7
- Personal Protective Equipment
Respiratory Protection: Use P2 dust filter in dusty conditions.
Hand Protection: Not required.
Eye Protection: Use safety glasses in dusty conditions.
Body Protection: Suitable clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance as delivered
Physical condition (form): Extruded edging
Colour: As requested by customer
Odour: Slight, characteristic
- Safety Data:
Decomposition temperature: > 280° C
Water solubility: Practically insoluble

10. STABILITY AND REACTIVITY

Stable under normal handling and storage conditions and when used in accordance with guidelines (see also Sections 7 and 8)

11. TOXICOLOGICAL INFORMATION

Not applicable

12. ECOLOGICAL INFORMATION

Non bio-degradable. When properly handled and used in accordance with guidelines our experience suggests there are no negative effects to be expected upon the environment.

13. DISPOSAL CONSIDERATIONS

Clean uncontaminated product may be disposed of by sale to reprocessors

Scrap materials may be disposed of at approved landfills or preferably by incineration under approved conditions

14. TRANSPORT INFORMATION

Product is not classified for any mode of transportation.

15. REGULATORY INFORMATION

This product does not require labelling according to the European Communities criteria or the Law on Hazardous Substances

- National Regulations:
Water Pollution Class: not hazardous to waters – self-assessment -

16. OTHER INFORMATION

The details printed here reflect the present state of our knowledge and experience and are based on information from our raw materials suppliers. They are a full description of our product with regards to its composition and use, but do not contain any guarantee regarding its characteristics. For terms of guarantee and liability see our General Conditions of Sale and Delivery.

These details reflect the present state of our knowledge and are meant to carry information on our products and their safety aspects. They are therefore not intended to serve as a guarantee of any given characteristics of the products or their suitability in any given case of application. All users of our products are themselves liable for observing any legal requirements, including those relating to accident prevention.

Döllken-Kunststoffverarbeitung GmbH
PO Box 440, D-45954 Gladbeck
Beisenstraße 50, D-45964 Gladbeck
Tel.: + 49 (0)2043/979-0
Fax: +49 (0)2043/979-587

Factory: Dunningen
PO Box 8, D-78653 Gladbeck
Daimlerstraße 4, D-78655 Dunningen
Tel. : + 49(0)7403/701-0
Fax. : + 49(0)7403/701-11

Chairman of the Board
Dr. Ing. Herbert Müller

Managing Directors
Dipl.-Ing. Oliver Beer
Dipl.-Kfm. Norbert Krupp
Hartwig Schwab

Bank details:
Commerzbank AG, Gladbeck
Deutsche Bank AG, Essen
Dresdner Bank AG, Essen

Sort Code	Acct. no.:
360 400 39	6 204 242
360 700 50	1 018 324
360 800 80	404 999 800

www.doellken.com
E-Mail: info@doellken.com

Comm.Reg. Gelsenkirchen 3935